

KB SERIES ENVIRONMENTAL CHAMBER

KB Series Overview

The KB Series chambers are a top selling environmental chamber. It is quiet, easy to clean, highly reliable and ideal for laboratory use. It offers hot gas bypass control of refrigeration and resistive heat to facilitate reliable, critical temperature and humidity control.

KB011

The KB011 is a bench top environmental chamber. Units can be stacked with optional racking set-up.

KB030

The KB030 is a 1-door environmental chamber.

KB034

The KB034 is a 1-door environmental chamber.

KB055

The KB055 is a 2-door environmental chamber.

KB068

The KB068 is a larger 2-door environmental chamber.

KB084

The KB084 is a 3-door environmental chamber.



KB SERIES: ENVIRONMENTAL CHAMBERS

The KB Series chambers feature hot gas bypass technology which controls the temperature of the epoxy coated evaporator for greater uniformity. Compressors in our KB Series of environmental chambers come with a three-year warranty, which is one of the longest in the industry. Compressors on the 011,034, and 068 are mounted on a removable lid for easier replacement. This helps for onsite repairs, not needing a burn permit to replace compressors. All these models run with 0.25 - 0.67hp compressors making them efficient enough to run on 15-amp, 115-volt circuits. KB Series includes a Multi-Port on every chamber. The Multipurpose Port can be used to add options to the chamber after the time of delivery, such as compressed dry air, desiccant wheel dryers or fresh air blowers. They also can be opened to release humidity, if necessary.

Superior Control and Uniformity

The ultrasonic humidification system provides excellent humidity control and avoids hot spots seen during chamber mapping of steam boiler equipped chambers. Standard control at the sensor in these chambers is $\pm 0.2^{\circ}\text{C}$ and $\pm 0.3\% \text{RH}$, uniformity that meets or exceeds ICH guidelines. All sensors are calibrated using NIST traceable standards before shipment of the chamber.

Options Available

- Extended Temperature Range**
- Chart Recorders
- Data Loggers
- Pneumatic & Desiccant Wheel Dryers**
- Window or Glass door. **
- Full swinging interior glass door
- Magnetic latch door handle with lock and two keys (011 and 034)
- Touch Screen interface
- Headless interface (Virtual Touch Screen VTS)
- Other control Options or monitoring i.e., CO₂.
- Adjustable Fan Speeds. **
- Air exchanges filtered or non-filtered with ambient space.**
- Condensate drain pumps.
- Interior or exterior electrical outlets. (Limited power) **
- Stainless Steel Exterior (030, 055 and 084)
- 5 gallon carboy (if no hookup to waterline available)
- Door ajar alarm

***Some Options may limit chamber performance less or greater than specified here.*

Greatly Reduced Direct and Indirect Energy Loads

The KB Series chambers utilize less energy than comparable stability chambers and introduce less impact upon building cooling systems. This efficiency “dual benefit” allows our chambers to be in spaces unsuitable for other chambers. Electrical energy savings by the KB Series vs. steam boiler equipped chambers can easily amount to hundreds or thousands of dollars saved per year. Based on Alarm event settings the chambers controller can optimize performance to use or not use compressor depending on set point temperature.

Widely Proven, Non-Proprietary Controllers


Standard controllers for the KB Series are manufactured by Fuji Electric and are ideal for stability testing chambers. Unlike many proprietary controllers, this controller is commercially available and proven in tens of thousands of installations. Standard functions include: autotuning, fuzzy logic, PID control, programmable alarms, calibration correction capability, ramp/soak, uniformity offset capability, etc. A touchscreen control interface is optional. Other controller manufacturers are also supported (Watlow, Allen Bradley etc.)

Services and Warranties

We offer technical support throughout the lifetime of your chamber. In addition to standard warranties, we also offer extended warranties for cooling components, parts, and labor. We also provide qualifications, validations, and preventive maintenance services at an additional cost.

KB Series Environmental Chamber Specifications (ambient 23° C)

		Temperature	
Performance	Standard	Optional	
Temperature Range	2° C to 50° C	-5° C to 70° C with Optional Defrost	
Ambient Temperature	21° C ± 3° C		
Temperature Control	± 0.2° C		
*Temperature Uniformity	± 0.7° C		
Control Resolution	0.1° C		
Temperature Sensor Type	3 wire PT100 Class A RTD		



* We place 5 sensors in the chamber, one in each corner (vertically) and one in the center. We log it overnight and look at the min to max across all points.


Humidity		
Performance	Standard	Optional
Humidity Range	Ambient Absolute Humidity* to 90% Relative Humidity @ 42°C Dewpoint	2 to 95% @ 22° C (or other ranges)
Humidity Control	± 0.3%	
Humidity Uniformity	± 2 %	
Control Resolution	0.1%	
Humidity Sensor	<p>Rotronic HC2A-S Operating range -50...100 °C / 0...100 %RH Accuracy: ±0.8 %RH, ±0.1 K, at 23 °C ±5 K Digital interface (UART) and scalable analogue outputs, 0...1 V</p> <p>RH Sensor Accuracy Overview</p>	Vaisala or other

*Absolute Humidity is the amount of moisture in the air in a particular environment.


The humidity chart below shows the chamber's humidity capabilities.

How to read the chart below:

The Humidity% Line in red is the max humidity level that can be achieved by staying within the 42°C dew point. Humidity levels above this line are not recommended. The Humidity Low line in green is the lowest the chamber can go without the use of a dryer. This is based on ideal performance and ambient condition of 23°C and 50% RH. Lower or higher ambient conditions will impact the lower humidity capabilities of your chamber. If your set points are near this line or below it is recommended to add dryer capabilities to your chamber. The Dryer Line in purple represents the use of a pneumatic dryer with a -40 Dew Point. To reach such low humidity, a constant supply of dry air is needed, and manual adjustment to humidity valve may be needed. Alternatively, if low %RH (low dewpoint) is desired but dry compressed air is not available, other dryer types are available.





*Humidity% represents chamber performing at 42°C Dew point.
 Humidity Low represents absolute humidity at ambient space of 23°C and 50%RH.*







Control System	Standard	Optional
Controller	Fuji PXF4	VTS (Virtual Touchscreen), Gefran 650, Future Design Controls CM and MCT4 + More
Control Readout	Actual and Set-Point Values 	Trending, Duty Cycle
Indication Accuracy	RTD input: $\pm 0.2\%$ of indication value ± 1 digit or $\pm 0.5^\circ\text{C} \pm 1$ digit, whichever is larger	Dependent on optional Controller
Sample Rate	Fast as 50 ms	Dependent on optional Controller
Control Speed	Fast as 100 ms	Dependent on optional Controller
Control Type	PID - Fuzzy Logic (9 types available)	Dependent on optional Controller
Auto Tuning	YES	Dependent on optional Controller
Calibration Correction Capability	± 0.1 lower and upper scale	Dependent on optional Controller
Uniformity Off Set	± 0.1 Resolution Linear adjustment	± 0.1 Resolution
Alarm	High / Low Audible and Visual	Text, Email, Web Server, Remote Access
Alarm Type	High / Low Deviation in 0.1 resolution with adjustable Delay. Control audible alarm enable or disable components.	Absolute & Deviation 0.1 Resolution with Delay
Remote Monitoring / BMS connection	Double throw Dry Contact Alarm, RS 485 MODBUS RTU / ASCII**	Ethernet & Analog Output (Specify voltage or mA)
Password Protection	Hexadecimal	Numeric, Alpha Numeric
Audit Trail	Not Standard*	Dependent on optional Controller
Universal Power Supply for Monitoring	Not Standard	Available. <i>Controllers and sensors powered during outage for data logging. Chamber operation not supported.</i>
Ramp Soak Function	Up to 64 steps. A Step includes a ramp and soak. Up to 8 patterns / programs (recipes).	Dependent on optional Controller

*Applies with touchscreen or VTS option.

**For BACNET or MODBUS TCP (Ethernet) please contact your BMS vendor about using a gateway to interface with controllers via the RS485.

	KB011	KB030	KB034	KB055	KB068	KB084
KB						
Construction						
Exterior	Powder Coated Finish	Stainless Steel Front continuous coil coated steel sides	Powder Coated Finish	Stainless Steel Front continuous coil coated steel sides	Powder Coated Finish	Stainless Steel Front continuous coil coated steel sides
Exterior Material Thickness	Heavy Gauge	Medium Gauge	Heavy Gauge	Medium Gauge	Heavy Gauge	Medium Gauge
Interior	304 Stainless Steel	Coated Aluminum	304 Stainless Steel	Coated Aluminum	304 Stainless Steel	Coated Aluminum
Interior Material Thickness	.036"	Medium Gauge	.036"	Medium Gauge	.036"	Medium Gauge
Door QTY	1	1	1	2	2	3
Door Lock	Optional	Tumbler Cam Key Lock	Optional	Tumbler Cam Key Lock	Optional	Tumbler Cam Key Lock
Door Swing	+180°	120° Stay Open Feature	+180°	120° Stay Open Feature	+180°	120° Stay Open Feature
Door Gasket	Magnetic Gasket	Snap in Magnetic Gasket	Magnetic Gasket	Snap in Magnetic Gasket	Magnetic Gasket	Snap in Magnetic Gasket
Shelving Material	304 Stainless Steel	Epoxy Coated	304 Stainless Steel	Epoxy Coated	304 Stainless Steel	Epoxy Coated
Shelf Quantity per Door	2	3	3	3	3	3
Casters Height	2.75"	3"	2.75"	3"	2.75"	3"
Caster QTY	4	4	4	4	5	4
Caster Locking Brakes	2	2	2	2	2	2
Access Port Qty	2	2	2	2	2	2
Multi-Purpose ports	YES	YES	YES	YES	YES	YES

Continuous coil coated is treated metal before it is cut and formed, the entire surface is cleaned and treated, providing tightly bonded finish. Formed sides have holes, valleys, recessed areas, and hidden areas that make it difficult to clean and uniformly coat. Coil coated metal is often considered more durable and corrosion resistant than most painted metal as it is treated before shaped.

	KB011	KB030	KB034	KB055	KB068	KB084
<h1>KB</h1>						
Capacity & Dimensions						
NET Capacity*	9.2 ft ³	22.1 ft ³	29.0 ft ³	48.2 ft ³	62.6 ft ³	74.3 ft ³
Conditioned Space	11.6 ft ³	23.9 ft ³	32.1 ft ³	50.0 ft ³	69.3 ft ³	76.2 ft ³
External Dimensions	36.2W x 27.4D x 47.1H	26W x 32D x 78.75H	35.7W x 33.8D x 80.8H	52W x 32D x 78.75H	68.4W x 34.2D x 81.8H	78W x 32D x 78.75H
Internal Dimensions	29.7W x 23.6H x 22.6D	22W x 28D x 62H	29.4W x 29.0D x 57.3H	48W x 28D x 62H	64.2W x 29.4D x 57.3H	74W x 28D x 62H
Access Port Dimensions	2" ID with Foam Insert	2" ID with Foam Insert	2" ID with Foam Insert	2" ID with Foam Insert	2" ID with Foam Insert	2" ID with Foam Insert
Recommended Clearance	Top 12"	Top 12"	Top 12"	Top 12"	Top 12"	Top 12"
	Rear 6"	Rear 6"	Rear 6"	Rear 6"	Rear 6"	Rear 6"
	Sides 6"	Sides 6"	Sides 6"	Sides 6"	Sides 6"	Sides 6"
Shelf Dimensions	28.9W x 20.4D	21.25W x 24.6D	28.75W x 26D	22.75W x 22.75D	31.4W x 24.25D	24W x 22.75D
Shelf Weight Capacity	150 lbs.	90 lbs.	150 lbs.	90 lbs.	150 lbs.	90 lbs.
Approx. Max Storage weight	600	500	700	1000	1000	1500
Approx. Crated Weight	470 lbs.	526 lbs.	765 lbs.	740 lbs.	1100lbs	1100 lbs.

	KB011	KB030	KB034	KB055	KB068	KB084
<h1>KB</h1>						
Components						
Compressor Size	1/3 hp	1/3 hp	1/3 hp	½ hp	½ hp	2 * 1/3 hp
Refrigerant	134a	134a	134a	134a	134a	134a
Charge (oz)	13.5 oz	13.5 oz	13.5 oz	18.5 oz	18.5 oz	13.5 oz
Defrost	Optional	Optional	Optional	Optional	Optional	Optional
Heater Watt Size	350	500	350	500	500	500 (1000)
Heater Qty	1	1	1	1	1	2
Perimeter Heater	YES	YES	YES	YES	YES	YES
Air flow direction	Front to Back	Front to Back	Front to Back	Front to Back	Front to Back	Front to Back
Fan Count	3	1	3	1	6	1
Fan CFM per fan	125	Up to 600	125	Up to 600	125	Up to 600
Variable Speed	Manual Adjust	Manual Adjust	Manual Adjust	Manual Adjust	Manual Adjust	Manual Adjust
Humidity	Yes	Yes	Yes	Yes	Yes	Yes
Water quality	A conductivity of 0.1 µS – 10 µS (Micro Siemens), TDS (Total Dissolved Solids) of less than 10 PPM (Parts per Million), and 1-10 PSI (Pounds per Square Inch) of supply water pressure. ¼" poly tube push to connect fitting for water connection.					
Max Water consumption	1200 ml / 0.32 Gal per Hour	1200 ml / 0.32 Gal per Hour	1200 ml / 0.32 Gal per Hour	1200 ml / 0.32 Gal per Hour	1200 ml / 0.32 Gal per Hour	1200 ml / 0.32 Gal per Hour
Water Connection	¼" poly tube push to connect	¼" poly tube push to connect	¼" poly tube push to connect	¼" poly tube push to connect	¼" poly tube push to connect	¼" poly tube push to connect
** Optional Compressed Dry Air **						
Max use 70 PSI & 200 CFH. ¼" poly tube push to connect fitting. Recommend Compressed Dry air of -40°C Dew point.						

	KB011	KB030	KB034	KB055	KB068	KB084						
<h1>KB</h1>												
Electrical North America												
Voltage	115 VAC/ 60 Hz										115/208-230 VAC /60HZ Chamber & 115 VAC /60Hz Dryer NEMA L14-20P	
RLA	8.0		6.5		8.0		12.0		12.0		12.0	
Heat Rejection	Low	High	Low	High	Low	High	Low	High	Low	High	Low	High
	1108 Btu/h	4392 Btu/h	1108 Btu/h	4392 Btu/h	1108 Btu/h	4392 Btu/h	1490 Btu/h	6122 Btu/h	1490 Btu/h	6122 Btu/h	2216 Btu/h	8784 Btu/h
Cord Length	9 ft		9 ft		9 ft		9 ft		9 ft		9 ft	
Dedicated Circuit	15 A		15 A		15 A		15 A		15 A		15 A	
Electrical International via Buck Boost Transformer												
Voltage	230 VAC/ 50 Hz											
RLA	4.0		3.3		4.0		6.0		6.0		6.0	
Heat Rejection	Low	High	Low	High	Low	High	Low	High	Low	High	Low	High
	1108 Btu/h	4392 Btu/h	1108 Btu/h	4392 Btu/h	1108 Btu/h	4392 Btu/h	1490 Btu/h	6122 Btu/h	1490 Btu/h	6122 Btu/h	2216 Btu/h	8784 Btu/h
Cord Length	2.74 m		2.74 m		2.74 m		2.74 m		2.74 m		2.74 m	
Accessory connections												
BMS Dry Contact	Screw terminal 3 position Common / Normally Closed / Normally Open											
RS485 MODBUS	1/8" or 2.5mm stereo input jack											
Optional Re transmission	Screw terminal											
Dry Air solenoid	Screw Terminal											
Desiccant Wheel Dryer	Twist lock 4 pin din connector											
Aux 24VDC output (500	5.2 mm Barrel Connector											

	KB011	KB030	KB034	KB055	KB068	KB084
<h1>KB</h1>						
mA limit)						

**Interior Capacity includes the 2" spacing from interior walls to allow for best air flow performance.*

***Include width with handle and height with castors installed.*

RLA and heat rejection is based on a controlled operation temperature of 30C and 65% RH. Value may change on operating set points.